

AW-209H/S AW-3328H/S AW-188H/S AW-3390H/S C-168H

Applications
DECT-Technology



AW-209H/S



AW-3328H/S



AW-188H/S



AW-3390H/S



C-168H

Specifications:

- Standard : DECT (Digital Enhanced Cordless Telecommunications)
GAP (Generic Access Profile)
- Radio Frequency range : 1880~1900 MHz
- Channel Space : 1728Khz // Bit rate : 1152Kbit/s
- RF channels : 10 Channels // Modulation : GFSK
- Voice coding : ADPCM,32Kbit/s // Transmitted power : 10mW

DECT Features:

- Call Transfer Between Handsets
- Handset can be registered to 4 Bases
- Intercom Call During External Call
- 4 Digits Handset & Base PIN
- Range - Outdoor : 300 Meters - Indoor : 50 Meters

Caller ID Features:

- Phonebook Memory 50 Locations // CID 50 Locations

Telephone Features:

- LCD:AW-3390H/S: 5*7 dot matrix // 12-Digits 2 line // 11 Symbols
AW-3328H/S: 1.5 inches, 65K Color graphic (resolution 128*128 pixels)
AW-188H/S: 1.5 inches, Mono graphic (resolution 128*64pixels)
- Hands-Free Function
- 12 Numeric Keys & 7 Function Keys // Low-Battery & Out-Of-Range Warning Display
- Support Multi Languages in Caller ID // Pulse/DTMF Dialing , FLASH Time
- 100 Hours Standby Time & 8 Hours Talk Time // Adjustable Ringer Volume & Melody)
- Dialing Pause Time (3/5 Seconds) // Call Duration Time, Mute Function
- Adjustable Receiver Volume(9 level) // 3*AAA Battery

Memory Features:

- Redial Memory // Caller ID Memory // Phonebook Memory