

DECT VoIP Cordless Phone

Support DECT & VoIP 2 CH

AW-206/206C/206T Traditional Chinese

Advantages:

- ✧ Great price for performance measure
- ✧ Best choice for Home and Office use
- ✧ Cost-saving // User friendly

Key Features:

- ✧ Make VoIP/ PSTN calls with a DECT phone
- ✧ Answer VoIP/ PSTN calls through any key on the phone pad
- ✧ Support intercom calls and paging function
- ✧ Support PSTN phonebook and Caller ID
- ✧ Support hands free and mute function

Product Specification:

- **Network Features**
 - DHCP client for WAN // DHCP server for LAN // Support PPPoE
 - Support static and dynamic IP // QoS for voice quality // DNS client
 - NAT and NAPT // HTTP Server // Support IP/TCP/UDP/RTP/RTCP
- **Protocols**
 - IP Version 4 RFC 791 and UDP // SIP RFC 3261 // SDP RFC 2327
 - DNS RFC 2782 // RTCP RFC 1889 // SNTP RFC 2030
- **Software updates**
 - Download of firmware/software updates through the protocols TFTP and HTTP
- **Configuration Features**
 - DHCP for network configuration (in either IP address, subnet mask, default gateway address, DNS client, TFTP client, NTP client etc)
 - Automatic download of configuration data through TFTP and HTTP
- **Management Features**
 - Upgrade firmware through web interface
 - Local and remote management using web interface
 - Command-Line Interface via a Telnet session
 - SNTP time setting // Event/Message Log (*not ready yet*)
- **Voice Features**
 - CODEC: G.711 A-law and Mu-law, G.723, G.726 and G.729
 - DTMF: In-band and RFC 2833 // Voice activity detection (VAD)
 - Comfort noise generation (CNG) // Silence threshold
 - Adaptive jitter buffer
- **DECT Specification**
 - Frequency: 1880 ~ 1900 MHZ or 1920 ~ 1930MHZ
 - Range: Outdoor - 300 Meters; Indoor - 50 Meters
 - Handset: 100 hours standby time & 10 hours talk time
 - Handset: Caller ID function (FSK & DTMF)
 - Handset: Phonebook memory 50 locations
 - Can register up to 6 Handsets
 - 2-port DECT
- **Hardware Features**
 - WAN: One RJ-45
 - LAN: One RJ-45
 - FXO: One RJ-11
 - PAGE and RESET button
 - Power: 6VDC 2.0mA
 - 1 FXO with 2 VoIP CH

AW-206

LCD: B&W



AW-206C

LCD: Color
w/ polyphonic
ring tone



AW-206T

LCD: B&W
w/ Chinese
characters



Application:

